



**deslaurier**  
CUSTOM CABINETS INC.

# Certificate of Warranty

## 1. GOODS FREE FROM DEFECTS

(a) Deslaurier Custom Cabinets Inc. (Deslaurier) warrants that all cabinetry and components excluding countertops (the Warranted Goods) manufactured by Deslaurier shall be free from defects in workmanship and materials when employed in normal residential use.

(b) This warranty does not include:

- i. any damage and/or deterioration due to normal wear and tear to the Warranted Goods arising from use;
- ii. any damage and/or defect attributed in whole or in part to the misuse, abuse or neglect of the Warranted Goods;
- iii. any deterioration and/or damage to the Warranted Goods attributable to the elements, including but not limited to exposure to sunlight, water or fire; and
- iv. any damage and/or defects attributable to any modification, alteration or correction of the Warranted Goods by any person not authorized by Deslaurier.

## 2. DURATION

This warranty shall be valid for a period of 20 years commencing on the date of installation except with respect to any thermo doors forming part of the Warranted Goods. Any thermo doors forming part of the Warranted Goods shall be warranted only for a period of 10 years from the date of installation.

## 3. SCOPE

This warranty is the sole warranty offered by Deslaurier and is available only to the original user of the Warranted Goods and cannot be assigned.

## 4. DUTIES OF THE USER

(a) For the duration of the warranty, in order to maintain this warranty in effect, the original user;

- i. must maintain the Warranted Goods in accordance with the prescribed maintenance instructions included herein;
- ii. must notify Deslaurier without delay of any defect in the Warranted Goods; and
- iii. must provide this Certificate of Warranty, properly completed.



deslaurier  
CUSTOM CABINETS INC.

## Caring for Your Cabinets

### **CABINET DOORS:**

Regular cleaning of wood should be done with a clean, damp cloth and dried immediately with a dry, soft cloth. Doors may require a coat of a high quality liquid or furniture paste wax. Thermo and laminated doors should be cleaned with a mild soap and water solution and dried immediately with a dry, soft cloth.

Do not use detergents, strong soaps, abrasives, or self-polishing waxes on your cabinets. Avoid using cloths which may contain remnants of these cleaners. Excess moisture is the worst enemy of any finish. Dry off any water immediately with a dry, soft cloth. Avoid exposure of doors and drawers with high heat.

Indoor relative humidity should be between 30 and 50%. As with any wood product, when humidity is low or fluctuates, cracking and splitting may occur.

### **CABINET INTERIOR:**

Regular cleaning of cabinet interiors should be done with a clean, damp cloth and dried immediately with a dry, soft cloth.

### **COUNTERTOPS:**

For general cleaning of laminated countertops use a soapy cloth. For stubborn stains, a non-abrasive liquid cleaner should be used. Avoid concentration of water or wet cloths at countertop's joints and seams. Excessive water standing in joints or seams may cause glue failure or delaminating. Hot pans or activated electrical appliances should not be placed on laminated surfaces. Always use protective insulating pads. Abrasive cleaners or steel wool should not be allowed to remain on the surface for any length of time. Use cutting boards. Please note that due to new house settlement the filler between the countertop and wall may come loose. Re-seal with Dap or Silicone caulking.